

RACE CLASS:	KART NUMBER:	ENGINE SEAL NUMBER:	DATE:

DRIVER INFORMATION:

DRIVER NAME: _____ AGE: _____ DOB: _____
 ADDRESS: _____ CITY: _____
 STATE: _____ ZIP: _____ COUNTRY: _____
 DAY PHONE: _____ EMAIL: _____

Used only for tech related communication. We will not spam or sell your information.

DIRECTIONS: PLEASE INDICATE COMPLIANCE FOR EACH ITEM BY CHECKING THE CORRESPONDING BOX. THIS FORM MUST BE SUBMITTED TO THE SUPERKARTS! USA PRE-GRID STEWARD PRIOR TO ENTERING THE TRACK FOR YOUR FIRST COMPETITION SESSION (WHETHER THAT BE QUALIFYING, HEAT OR MAIN). FAILURE TO DO SO MAY RESULT IN A PENALTY ASSESSMENT, AS DETERMINED BY THE RACE OR TECH DIRECTOR.

ITEMS THAT NEED TO BE SECURED BY NYLOCK, SAFETY WIRE, COTTER PINNED, OR SECURED BY CIRCLIP OR SNAP RING:

GENERAL SAFETY REQUIREMENTS WHICH MUST BE ADHERED TO:

STEERING ASSEMBLY

- STEERING WHEEL TO HUB BOLTS
- STEERING HUB TO SHAFT BOLT
- STEERING SHAFT TO CHASSIS
- TIE ROD END BOLTS
- KINGPIN BOLTS
- SPINDLE NUT ATTACHING WHEEL

BRAKING SYSTEM

- PEDAL PIVOT TO CHASSIS
- ACTUATING ROD AND CABLE ENDS
- MASTER CYLINDER TO CHASSIS BOLTS
- CALIPER(S) TO CHASSIS BOLTS
- PAD RETAINING RODS
- BRAKE ROTOR TO HUB
(METAL LOCKNUTS ONLY)

OTHER SAFETY ITEMS

- THROTTLE PEDAL PIVOT TO CHASSIS
- WEIGHT MOUNTING BOLTS
(DOUBLE NUTTED OR DRILLED WITH THE NUT SAFETY-WIRED/COTTER PINNED)

MAXIMUM OVERALL DIMENSIONS OF KART THAT MUST BE IN COMPLIANCE:

KART WIDTH AND LENGTH

- MAXIMUM WIDTH – 55 1/8 INCHES
(MAX WIDTH FOR MICRO/MINI SWIFT – 50" / 1270MM)
- MAXIMUM LENGTH – 84 INCHES



BY SIGNING THIS I PRESENT THIS KART AND DOCUMENT AND CERTIFY THAT ALL ITEMS ON THIS FORM HAVE BEEN COMPLETED, VERIFIED AND WILL BE MAINTAINED IN ACCORDANCE WITH THIS DOCUMENT FOR THE REMAINDER OF THIS EVENT.