



# PRE-TECH CERTIFICATION

REVISION: 2018 WINTER SERIES

RACE CLASS: \_\_\_\_\_

KART NUMBER: \_\_\_\_\_

ENGINE SEAL NUMBER: \_\_\_\_\_

CHASSIS TAG NUMBER: \_\_\_\_\_

DATE: \_\_\_\_\_

## DRIVER INFORMATION:

DRIVER NAME: \_\_\_\_\_ AGE: \_\_\_\_\_ DOB: \_\_\_\_\_

ADDRESS: \_\_\_\_\_ CITY: \_\_\_\_\_

STATE: \_\_\_\_\_ ZIP: \_\_\_\_\_ COUNTRY: \_\_\_\_\_

DAY PHONE: \_\_\_\_\_ EMAIL: \_\_\_\_\_

Used only for tech related communication. We will not spam or sell your information.

**DIRECTIONS: PLEASE INDICATE COMPLIANCE FOR EACH ITEM BY CHECKING THE CORRESPONDING BOX. THIS FORM MUST BE SUBMITTED TO THE SKUSA PRE-GRID STEWARD PRIOR TO ENTERING THE TRACK FOR YOUR FIRST COMPETITION SESSION (WHETHER THAT BE QUALIFYING, HEAT OR MAIN). FAILURE TO DO SO MAY RESULT IN A PENALTY ASSESSMENT, AS DETERMINED BY SKUSA.**

ITEMS THAT NEED TO BE SECURED BY NYLOCK, SAFETY WIRE, COTTER PINNED, OR SECURED BY CIRCLIP OR SNAP RING:

### GENERAL SAFETY REQUIREMENTS WHICH MUST BE ADHERED TO:

#### STEERING ASSEMBLY

- STEERING WHEEL TO HUB BOLTS
- STEERING HUB TO SHAFT BOLT
- STEERING SHAFT TO CHASSIS
- TIE ROD END BOLTS
- KINGPIN BOLTS
- SPINDLE NUT ATTACHING WHEEL

#### BRAKING SYSTEM

- PEDAL PIVOT TO CHASSIS
- ACTUATING ROD AND CABLE ENDS
- MASTER CYLINDER TO CHASSIS BOLTS
- CALIPER(S) TO CHASSIS BOLTS
- PAD RETAINING RODS
- BRAKE ROTOR TO HUB  
(METAL LOCKNUTS ONLY)

#### OTHER SAFETY ITEMS

- THROTTLE PEDAL PIVOT TO CHASSIS

MAXIMUM OVERALL DIMENSIONS OF KART THAT MUST BE IN COMPLIANCE:

#### KART WIDTH AND LENGTH

- MAXIMUM WIDTH – 55 1/8 INCHES  
(MAX WIDTH FOR MICRO/MINI SWIFT – 50" / 1270MM)
- MAXIMUM LENGTH – 84 INCHES

#### MG RACE TIRES (ENTER SERIAL NUMBERS)

01  02  03  04

- CIK-SPECIFICATION BRAKE SAFETY CABLE WITH A MINIMUM DIAMETER OF 1.8MM
- BRAKE FUNCTIONALITY TEST - SUFFICIENT FORCE APPLIED TO BRAKE PEDAL SHALL RESULT IN ALL APPLICABLE WHEELS BEING UNABLE TO TURN
- HELMET MEETS LATEST SKUSA RULES. PLEASE ENTER THE HELMET RATING FROM THE INSIDE OF YOUR HELMET HERE \_\_\_\_\_
- SEAT MOUNTING TABS AND STRUTS IMPLEMENTED PER INTENT OF CHASSIS MANUFACTURER
- FUNCTIONAL FUEL AND WATER RECOVERY SYSTEM
- BODYWORK MOUNTED AS INTENDED BY MANUFACTURER
- APPROPRIATE KART NUMBER, COLOR AND BACKGROUND (4 LOCATIONS)
- REAR PROTECTION MEETS CURRENT SKUSA RULES
- WEIGHT(S) (BALLAST) PAINTED WHITE
  - WEIGHT(S) UNDER 7 LBS. SECURED BY (1) 5/16" / 8MM BOLT
  - WEIGHT(S) 7+ LBS. SECURED BY TWO (2) 5/16" / 8MM BOLTS
  - DOUBLE NUTTED OR DRILLED WITH BOLT SAFETY-WIRED OR COTTER PINNED
- RECOMMENDED: METAL SEAT/SEAT STRUT REINFORCEMENT WASHERS - MIN 35MM DIAMETER
- STARTER BATTERIES LABELED WITH KART # AND CLASS, AND MOUNTED PER SKUSA RULE 20.3.4.3



BY SIGNING THIS I PRESENT THIS KART AND DOCUMENT AND CERTIFY THAT ALL ITEMS ON THIS FORM HAVE BEEN COMPLETED, VERIFIED AND WILL BE MAINTAINED IN ACCORDANCE WITH THIS DOCUMENT FOR THE REMAINDER OF THIS EVENT.